

Microprocessor controlled MIG-MAG/FLUX/BRAZING/MMA/ TIG DC-Lift inverter multiprocess welding machine. Technomig Dual Synergic is confirmed as the perfect solution for a wide range of applications, from maintenance to installation and interventions in body shops, because of its flexibility and the different materials it can weld (steel, stainless steel, aluminium) or braze weld (galvanized sheet). The quick SYNERGIC regulation of the welding parameters, thanks to the ONE TOUCH LCD SYNERGY technology, makes this product easy to use. The intelligent and automatic control of the arc, moment by moment, maintains high welding performance in all working conditions, with different materials and/or gases. The operator can also intervene manually along the arc length: this adjustment means the weld seam can be modified according to the welder's style. The ONE TOUCH LCD graphic display allows for a better reading of all welding parameters. Lightweight and very compact, Technomig can be moved around easily in all intervention areas, both indoors and outdoors. Main features: polarity reversal for GAS MIG-MAG/BRAZING welding \* 17 synergy curves available \* visualization on LCD display of voltage, current, welding speed \* regulation of: wire speed up slope, electronic reactance, burn-back time, post gas \* choice of 2/4 times, spot operation \* thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator\* ( $\pm 15\%$ ) protections. Fit for NO GAS/Flux welding, it can be transformed into MIG-MAG with the optional kit.



PROFESSIONAL



**MIG-MAG/TIG/MMA MULTIPROCESS**

**ONE TOUCH LCD SYNERGY** EASY TO SET, EASY TO WORK!

WELDS FE,SS,AL,GALVANISED SHEETS

**MIG-MAG**

LETTURA IMMEDIATA DI TUTTI I P

**SYNERGY**

17 PRE-SET SMART CURVES

**SYNERGY**

SEAM CAN BE SHAPED AS REQUIRED

**FINE SET**

OPTIONAL KIT RUOTE

Norms:

V <sub>ph</sub>	A <sub>MIN</sub>	A <sub>MAX</sub>	A <sub>60%</sub>	V <sub>o</sub>	A <sub>60% MAX</sub>	P <sub>60% MAX</sub>	η	φ	ST
V50/60Hz	A	EN60974-1	EN60974-1	V	A	kW	n%	cosphi	mm
230 1 ph	20 220 DC	180 20% DC	105 DC	62	16 31	2,6 5,2	86	0,7	0,6 1
SS	AL	FX	BZ	IP	W <sub>L</sub>	W <sub>L</sub>	kg	BAR CODE	
mm	mm	mm	mm		cm(L,W,H)	inch	kg		
0,8	0,8 1	0,8 1,2	0,8	IP23	57 27 48 (senza)	77 27 60 (con)	22(senza ruote),25 (	8004897917 63 4	