

# ROMESS®



**MADHUS**  
Garage Equipments

[www.madhusindia.com](http://www.madhusindia.com)

NO.46/2,DODDAKALLASANDRA, KONANAKUNTE CROSS,  
KANAKAPURA ROAD, BANGALORE-560062  
PH : +91-80-26666026 / +91-80-26666516 /  
+91-80-2666513 / +91-80-26660656  
FAX : +91-80-26666033.

- Brake Maintenance
- Mineral oil ventilation (HY-devices)
- Vehicle gauging
- Tyre service
- Engineering



Order-No.: **1003**

Type: **SE 3**



The **SE 3** is a portable brake maintenance device with an internal ca. 5 l tank and ca. 1 l reserve. Therefore the device is designed for mobile applications.

With this device hydraulic brake systems and hydraulic clutches of passenger cars, commercial vehicles and motorcycles can be maintained.

By a one man operation the brake-fluid change is easy and without problems.

With this device the brakes can be rinsed, ventilated and filled.

Control of the operation pressure and of the minimum fill level via red signal lamp.

## Description:

**Electrical powered pump:** After switching-on the pump the pressure builds up slowly. This prevents a „foaming“ of the brake fluid with air because of the small flow velocity and the built-in return, which also gives a bubble free transportation.

**Automatic switch-off** of the pump when reaching the minimal capacity. Therefore no air will get into the hydraulic system.

**The red signal lamp is on as long as the pump is building pressure.**

During operation, this signal lamp is turned off and only lights up again when the pressure falls off or the minimum level is reached and the tank has to be refilled.

**Infinitely adjustable pressure regulation** from about 0.5 to 2.0 bar (maximal 2.4 bar) with manometer indication.

**Pulsating liquid current** of the brake-fluid. These oscillations make a complete ventilation of the pipes possible, because even the smallest air- and humidity locks at the pipe walls are getting carried away.

**Automatically pressure decreases** when switching off the device. The device can be disconnected from the adapter without pressure by the quick coupling. There is no overflow of the brake fluid.

The 3.5 m long inflating hose makes the ventilation possible on every car lift without any problems.

**Simple handling**, no training is necessary, uncomplicated refilling.

**Suitable for ABS-brake systems.**

## Technical Data:

Electrical connection: 230 V/50 Hz (for S 2 optional 12 V)

Dimension of device (W x D x H) in mm: ca. 310 x 500 x 480

Dimension of delivery (W x D x H) in mm: ca. 355 x 520 x 520

Weight of device: about 9.0 kg

Weight of delivery: about 13.0 kg

## Order-No.:

1003

## Scope of delivery:

Device model SE 3, filling hose with quick-lock couplings, mains cable with plug with protective contact, warranty card and operation manual.

## Accessory:

Catch bottle (50256), standard adapter (50232) and adapters for almost all vehicles.

Complete disposal system for used brake fluid.

**Modifications and errors reserved, 09/01/2012**